LED Tube Light T8 -10W DATASHEET





INDEX

Product Bases	1
Product Picture	2
Technology Parameter	3
Power Supply (SMPS) Parameters And Connection	4
Product Drawing	5
Installation	6
Packaging	7
Application	

1- Product Bases

Contains 1 PCBs with 48 Pcs Of LED Light Source 2835 LG Innotek

Made In Korea each Chip Produces 110 LM/W.


High Transparency PS LED Cover - Out Case of Aluminum.

LED PSU based on flicker free, 0.92 PF - No over heat type

2 - Product Pictures

3 - Technology Parameter

Spectrum Of Light:



Model:	LED Tube light 600mm	10W	Type	Indoor Lighting	
Product Name:	T8-10W Tube Light		LED Type	LG Innotek	
Application:	Office / Commercial		LED P/N	EGY-10W-114	
Input Voltage	/oltage AC 10		0-277 V - 50/60 Hz		
Light Input Volta	age	DC 12 - 32 V			
Color Temperat	ure	4000K / 5700K			
Total Power (W)	ver (W)		10 ± 5%		
Total Flux (Lm)	tal Flux (Lm)		>1000		
Efficacy (Lm/W) 100					
CRI	>80				
Beam Angle	Seam Angle 120°				
Power Factor		0,92			
IP		IP20			
Operating Temperature -20 °C to +50 °C					
Storage Temper	Storage Temperature		-20 °C to +60 °C		
Life	Life		50.000 Hours		

Datasheet is subject to change without notice last up date at Nov. 2019.

4 - SMPS Technology Parameter

Integrated Constant Current Source for LED driver



Features

- High efficiency
- Compact size
- AC184-264V wide input voltage range
- Constant current output
- Isolated Input-Output
- Low output ripple current & Voltage
- Built-in Output Short Protection
- Flicker free IC integrated

5 - Product Drawing

6 - Installation

7- Packaging

Cartoon Box 62.50 X 31 X 20.50 including 40 pcs of Tube 600mm each Tube In a Crash resists Cylinder Carton

8 - Applications

- OfficeShopElevatorsBank
- Hospital Entrance Parking Garage

Datasheet is subject to change without notice last up date at Nov. 2019.